

The POWERMOVER 2000 (PM2K) is a compact, highly maneuverable industrial cart mover. It combines i) the hydraulic lift system of a manual jack with ii) a unique, quick-connect hitching system and iii) the POWERPALLET 2000 (PP2K) drive system ... together creating a fast, powerful, easy-to-use and highly maneuverable cart mover. Connecting via the mating cart hitch (attached to each cart) it allows a single operator to effortlessly move wheeled loads weighing up to 3,500lbs (1,600kgs).

FASTER: The POWERMOVER 2000 features a self-aligning quick-connect/quick-disconnect hitching system. Additionally, it features a user settable max. speed of 3.7mph (100m/min) and infinitely variable throttle for both forward (pushing) and reverse (pulling).

MORE POWERFUL: Utilizing the same drive system as on the POWERPALLET 2000, the POWERMOVER 2000 can move 3,500lb (1,600kg) with ease, or for loads weighing even more, it becomes a powered assist that does most of the heavy lifting.


MORE MANEUVERABLE: With more than 180° of directional rotation at the hitch and a footprint less than 11" (275mm) wide at full turn, the PM2K offers exceptional maneuverability in tight spaces. Additionally, the PM2K is intuitive and easy-to-use either pulling or pushing loads.

MORE FLEXIBLE: The PM2K employs a unique spring compliance system for hitching. The operator can engage but only lift enough to compress the spring and provide traction, or pump more and lift the hitched end of the cart entirely off the ground. This is ideal for two-wheeled / two-legged carts, poorly running carts or for operation on uneven / low-traction floors.

SAFER TO USE: A unique feature of the PM2K is its automatic pin locking system that ensures a secure connection between cart and mover. A spring-loaded pin locks the PM2K's hitch to the cart's hitch preventing the two from separating - regardless of the terrain or use case. The locking pin is also automatically retracted when the cart is unhitched.



The cart hitch (included) can be mounted onto any wheeled cart.



Quick-change battery packs & charger



BETTER VALUE: Despite the exceptional performance, features and reliability, the PM2K costs less than most movers in its class. And as the PM2K and PP2K share not just the same operating method, but also the same key componentry (including operator controls, battery packs and chargers), these two series are also perfect partners in facilities that utilize **both** carts and pallets.



PowerHandling Inc. endeavors to ensure that all information provided in this data sheet is correct at the time of its publication, however it takes no responsibility for the accuracy, currency, reliability or correctness of said information. All capacities described are estimates and depend on factors such as the rolling resistance of the wheels / castors in use, the flatness and condition of the surface being rolled over, etc. Each specific application should be tested to confirm performance. (Ver. 2017/03)

PM2K SPEC'S	Max. Speed*		Load Moving Capacity		Drive Motor	NiMH Battery Pack		Recharge Time
	M/Min	MPH	Kg	Pounds		Amp Hours	Voltage	
	100	3.7	1,600	3,500	Brushless DC	5Ah	45.6V	2 hours (from 80% depletion)